

**Model No. : COR-BIMCO-FL**

Model No.	:	COR-BIMCO-FL
Media compatibility	:	Compressed air (dry), N2 Gas, oxygen OR Any Gas except C ₂ H ₂
Pipe diameter	:	DN25 –DN400
Flow velocity range	:	0.9~90Nm/s
Accuracy	:	1.5%RD+0.5%FS
Flange	:	ASA 150 # RF of SS.304
OutPut/transmitter	:	Frequency (pulse)/4-20mA with Bluetooth as standard
Communication	:	RS-485 as standard, 4~20mA@HART As (optional)
Temp. of Gas	:	- 40° C to +150° C Max
Pressure Of medium	:	Max 16 Bar
Display	:	Flow rate & Total flow
Data display	:	Mass flow, volume flow in normal condition, Total flow, temperature of medium, velocity.
Power Supply	:	DC16~32V OR AC85~264V, 24VDC
IP grade	:	IP65
Sensor	:	SS.316
Other wetted parts	:	SS.304
Head	:	Aluminum
Make	:	BIMCO
Other details as per attached file		

Manufactured & Marketed By :
M/S. Bombay Instrument Mfg. Co.

SHOP NO. 5 , 50/86, JITEKAR WADI
OPP. VINAY HOTEL 88, THAKURDWAR ROAD MUMBAI – 400 002 - INDIA
Tel. : 91 (022) 2389 1073 / 2389 10 7 5
Fax : 91 (022) 2389 1075
Web. : www.bombayinstrument.in
Email : bimco@mtnl.net.in , bimcoindia@gmail.com
