

**OGM-D-SERIES****OGM-25/40/50 FLOW METER****OGM-D-25/40/50 ALUMINUM OVAL GEAR****METER WITH ELECTRONIC REGISTER**

OGM-D SERIES Cast Electronic Flow Meter Is Used To Transfer Large Viscosity Range Of Liquids, And Has Good Repeatability And Life, Can Be Widely Used In Petroleum, Chemical, Pharmaceutical, Transportation food To Be Industrial And Commercial. **OGM-D SERIES** Aluminum Oval Gear Meter Has The Ability to Handle A Wide Range Of Fluid Viscosities With Exceptional Levels Of Repeatability And Durability, Applying In The Petroleum, Chemical, Food Industry, Etc.

ADVANTAGES Small Pressure Loss, Compact Structure, Easy Maintenance, Easy To Read LCD Display And Easy To Operate, Flexible Horizontal Or Vertical Installation, Flange And Threaded Connections.

TECHNICAL DATA

Model:	OGM-D-25	OGM-D-40	OGM-D-50
Size:	1 "	1 ½ "	2 "
Min. Flow Rate:	20L/min	25L/min	30L/min
Max. Flow Rate:	120L/min	250L/min	300L/min
Accuracy:	± 0.5%	± 0.5%	± 0.5%
Repeatability:	≤ 0.03%	≤ 0.03%	≤ 0.03%
Max. Viscosity:	1000CPS	1000CPS	1000CPS
Max .Operating Pressure:	3.4MPa	1.8MPa	1.8MPa

ADVANTAGES

- Low pressure drop
- Compact size, easy maintenance
- Easy to read and operate mechanical display
- Horizontally and vertically flexibility of installation options
- 5-digital sub-total, with floating point from 0.01 to 99999.99, 7-digital non-Resettable totalizer.
- 3.6V lithium battery power, durable service

Manufactured & Marketed By :
M/S. Bombay Instrument Mfg. Co.

SHOP NO. 5 , 50/86, JITEKAR WADI
 OPP. VINAY HOTEL 88, THAKURDWAR ROAD MUMBAI – 400 002 - INDIA
 Tel. : 91 (022) 2389 1073 / 2389 10 7 5
 Fax : 91 (022) 2389 1075
 Web. : www.bombayinstrument.in
 Email : bimco@mtnl.net.in , bimcoindia@gmail.com