

## VACCUM MANOMETER



### **MODEL : HUM - 450 + SP-45**

1. "BOMBAY INST. MFG. CO." Make Industrial grade, High accuracy, Wall mounting, Full High Vacuum Manometer with detail specification as follows.

Our Model No.	: HVM-450-SP-45
Type	: Wall mounting type
Min. Division	: 1MM Hg.abs
End fitting & Block	: SS.304
Connection	: 6mm Ferrule
Tube	: 9x4mm, Heavy wall Borosilicate
Casing	: Aluminium body from 3 sides & clear acrylic front.
Drain Plug	: 1/4" NPT
Scale	: Engraved on milky white acrylic .Engraving filled with black colour slot for scale Zero adjustment will be provided.

#### **DETAILS OF CATCHPOT :**

Above manometer inbuilt with catchpot suitable to collect dust, moisture in your suction line complete with isolating valve with screwed connection at top (your process) & drain plug at bottom

Top & Bottom Block	: Of M.S.
Glass Pipe	: 2" O.D. x 90mm long
Protective cum tie Rods	: of Brass,4 Nos,
Drip Pipe	: of SS.304
Isolating Valve	: Of SS..304
Connection to Instrument	: 15mm BSP(M)
Range	: 100-0-100mm Hg.abs.
Qty.	: 1 Nos.

**REMARK :** Only above type manometer is suitable for direct measurement of mm Hg.abs. (Torr) reading. Single limb manometer uses for measurement of mm Hg. reading only.

